

Section 1 IDENTIFICATION

Product Name: Acrylic Seaming Adhesive

Manufacturer: American Acrylic Adhesives
 2020 Wild Acres Rd., Building D
 Largo, FL 33771
 Phone: 1-877-422-GLUE
 Email: jeff@aaaglu.com Website: www.aaaglu.com

Trade Name: Everform™ Solid Surface Seam Adhesive


Seaming Adhesive

Materials Uses: Seaming Adhesive for solid surfacing, engineered stone, quartz and natural stone

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA & Canada)

Section 2 HAZARD IDENTIFICATION
--

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Physical Flammable Liquids, Category 2 Organic Peroxide, Type B	DANGER	H225 – Highly flammable liquid and vapor
Health Acute Oral Toxicity, Category 4 Skin Irritation, Category 3 Eye Irritation, Category 2B Skin Sensitization, Category 1	WARNING WARNING WARNING WARNING	H302 – Harmful if swallowed H316 – Causes mild skin irritation H320 – Causes eye irritation H317 – May cause an allergic skin reaction
Environmental Acute, Category 3 Chronic, Category 4		H402 – Harmful to aquatic life H413 – May cause long lasting harmful effects to aquatic life
		

GHS Precaution Statements:

Prevention:

- P210 – Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P261 – Avoid breathing dust/fume/mist/vapors/spray.

- P264 – Wash hands (or other affected skin surfaces) thoroughly after handling.
 P270 – Do not eat, drink, or smoke when using this product.
 P273 – Avoid release to the environment
 P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P370/P378 – In case of fire: Use dry chemical or CO₂ to extinguish
 P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P301/P312 – IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
 P302/P352 – IF ON SKIN: Wash with plenty of soap and water.
 P333/P313 – If skin irritation or rash occurs get medical advice/attention.

Storage:

- P403 – Store in a well-ventilated place.
 P410 – Protect from sunlight.
 P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

- P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations.

Route of Entry: Eye contact, skin contact, inhalation, and ingestion.

Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.



Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.


Ingestion: Not an expected route of entry. If ingested it may cause irritation to the gastrointestinal tract.

ADHESIVE:
HMIS (United States)

Health 2
 Flammability 3
 Reactivity 2
 PPE B

NFPA (United States)

WHMIS (Canada): B2, D2B

ACTIVATOR:
HMIS (United States)

Health 2
 Flammability 3
 Reactivity 2
 PPE B

NFPA (United States)

WHMIS (Canada): C, D2B


Section 3 COMPOSITION / INFORMATION ON INGREDIENTS

	Name	CAS #	% by Weight
Adhesive:	Methyl Methacrylate Monomer	80-62-6	40 – 70
	Methacrylic Acid	79-41-4	1 – 5
Activator:	Benzoyl Peroxide	94-36-0	5 – 15

Section 4 FIRST-AID MEASURES

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

Eye: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.

Respiratory: Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Seek immediate medical attention.

Ingestion: Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire, use dry chemical or CO₂. Water spray may cause frothing.

Specific Hazards Arising from the Chemical: Sealed containers of adhesive may rupture violently at elevated temperatures due to polymerization. Organic peroxides can decompose violently if heated while confined.

Special Protective Equipment and Precautions for Firefighters: Use self-contained breathing apparatus (SCBA) and protective clothing.

Flash Point and Method: 50°F (10°C). Fine mists may be explosive below the flash point. Tag Closed Cup.

Flammability Classification: Class 1B.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable.

Hazardous Products of Combustion: Carbon Oxides (CO and CO₂), Methyl Methacrylate, and various Hydrocarbons.

Autoignition Temp.: 790°F (421°C).

LEL: 1.7%.

UEL: 12.5%.

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: For large spill or leak wear self-contained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Keep out of sewers and drains.

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7	HANDLING AND STORAGE
------------------	-----------------------------

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Store in a cool, dry, well-ventilated area at temperatures less than 75°F (25°C). Storage above 212°F (100°C) may cause explosive decomposition. Avoid storage in direct sunlight. Keep containers closed when not in use. Keep away from heat sources, sparks, and open flames.

Section 8	EXPOSURE CONTROLS / PERSONAL PROTECTION
------------------	--

Control Parameters and Exposures:

Material Name:	Exposure Limits:
Benzoyl Peroxide (CAS 94-36-0):	OSHA PEL: TWA 5 mg/m ³
	ACGIH TLV: TWA 5 mg/m ³
Methacrylic Acid (CAS 79-41-4):	ACGIH TLV: TWA 20 ppm
Methyl Methacrylate (CAS 80-62-6):	OSHA PEL: TWA 100 ppm
	ACGIH TLV: TWA 50 ppm
	STEL 100 ppm

Engineering Controls: Provide adequate explosion proof ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area.

Individual Protection Measures and PPE:

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended.

Respiratory Protection In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

	Adhesive	Activator
Appearance:	Colored (various) Paste	Liquid
Odor:	Mild Sweet	Mild Sweet
Odor Threshold:	Not Available	Not Available
pH:	4.0 – 6.0	4.0 – 6.0
Melting Point / Freezing Point:	-54°F (-48°C)	Not Available
Initial Boiling Point and Boiling Range:	212°F (100°C)	> 550°F (288°C)
Flash Point and Method:	50°F (10°C) Tag Closed Cup	Not Available
Evaporation Rate:	3	<1 (butyl acetate = 1)
Flammability:	Class 1B	Class 1B.
Lower Explosion Limit:	1.7%	Not Available
Upper Explosion Limit:	12.5%	Not Available
Vapor Pressure:	28 mm Hg @ 68°F (20°C)	< 0.5 mm Hg @ 68°F (20°C)
Vapor Density:	3.5	Not Available

Relative Density:	7.7 – 8.8 lbs./gallon	Not Available
Solubility(ies):	Not Available	Not Available
Partition Coefficient (n-Octanol in Water):	Not Applicable	Not Applicable
Auto-Ignition Temperature:	790°F (421°C)	Not Available
Decomposition Temperature:	Not Available	Not Available
Viscosity:	Not Available	Not Available
Percent Volatile:	Not Available	Not Available
Specific Gravity:	0.93 – 1.05	Not Available
VOC:	< 50 g/L of mixed product	Not Available
Composition:	Formaldehyde Free Phthalate Free	Formaldehyde Free Phthalate Free

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable as supplied and when used as intended. Product can become unstable under certain conditions or in contact with incompatible materials.

Chemical Stability: Not Available.

Possibility of Hazardous Reactions: Polymerization may occur under certain conditions.

Conditions to Avoid: Avoid extreme temperatures, open flames, sparks, and direct sunlight.

Materials to Avoid (Incompatibility): Oxidizing agents and conditions, strong acids and alkalis, oxygen-free atmospheres, inert gas blanketing, and free radical initiators.

Hazardous Decomposition Products: Carbon Oxides (CO, CO₂), Methyl Methacrylate, and various Hydrocarbons.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Adhesive: Methyl Methacrylate (CAS 80-62-6):	LC50 = 7093 ppm (4 hour inhalation, rat) LD50 = 7940 mg/kg (oral, rat) LD50 > 7550 mg/kg (dermal, rabbit)
Methacrylic Acid (CAS 79-41-4):	LC50 = 7100 mg/m ³ (4 hour inhalation, rat) LD50 > 7550 mg/kg (oral, rat) LD50 = 1600 mg/kg (oral, mouse) LD50 > 500 mg/kg (dermal, rabbit)
Activator: Benzoyl Peroxide (CAS 94-36-0):	LC50 = 2 mg/L (96 hour inhalation, guppy) LD50 = 6400 mg/kg (oral, rat) LD50 > 2000 mg/kg (oral, mouse)

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information.

Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information.

Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information.

Skin Corrosion / Irritation: Not Available.

Eye Damage / Irritation: Not Available.

Respiratory Sensitization: Not Available.

Skin Sensitization: Not Available.

Mutagenicity: Classifiable as "none" for human.



Carcinogenicity: Not classifiable for human or animal.
Reproductive Toxicity: Not Available.
Teratogenic Effects: Classifiable as “none” for human.
STOST- Single Exposure: Not Available.
STOST – Repeated Exposure: Not Available.
Aspiration Hazard: Not Available.

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: This product contains components that may be harmful to aquatic organisms and may cause long term adverse effects in an aquatic environment.
Persistence and Degradability: Not Available.
Bioaccumulative Potential: This product contains components with the potential to bio-accumulate.
Mobility in Soil: Not Available.
Other Adverse Effects: Not Available.

Section 13 DISPOSAL CONSIDERATIONS

Disposal Methods:
Adhesive: Adhesive is considered Hazardous Waste Product per RCRA 40 CFR 261 and is classed as D001. Spilled, contaminated, or waste material should be put into a suitable container and handled according to Federal, State, and local regulations. Contact a qualified waste management company for assistance.
Activator: Not a hazardous waste product (RCRA 50 CFR 261). May be disposed of by landfill or incineration. Dispose of in accordance with Federal, State, and local regulations.
DANGER! Rags, steel wool, and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. Waste should be immediately placed in a sealed water filled container.

Section 14 TRANSPORT INFORMATION

UN Number: UN1133.
UN Proper Shipping Name: Adhesives (DOT), Flammable Liquid.
Transport Hazard Class: 3.
Packing Group: II.
DOT Classification: UN1133, Adhesives, Flammable Liquid, Hazard Class 3, Packing Group II, Limited Quantity.
Special Provision for Transport: 1 Liter (0.3 gallon) or less may use Limited Quantity exceptions (49 CFR 172.102 & 49 CFR 173.150 (a) (2)).
ADR / RID Classification: Class 3 Flammable Liquid.
ICAO/IATA Classification: Class 3 Flammable Liquid.
IMO/IMDG Classification: Class 3 Flammable Liquid.
Marine Pollutant: No additional information.

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations

Chemical (& CAS Number)	SARA 302 (EHS)TPQ	SARA 304 (EHS)Rq	SARA 313 <i>de minimis</i>	CERCLA Rq	CAA 112(r) TQ	RCRA Code
Benzoyl Peroxide (CAS 94-36-0)			1.0			



SDS Safety Data
Sheet
Number:
Page 7 of 7

Acrylic Seaming Adhesive

Revision Date:05/06/2021

Methyl Methacrylate (CAS 80-62-6)			1.0	1000		U162
Methacrylic Acid (CAS 79-41-4)						

All quantities in pounds.

State Regulations

Chemical (& CAS Number)	CA Prop 65	MA RTK	MN RTK	NJ RTK	PA RTK	RI RTK
Benzoyl Peroxide (CAS 94-36-0)		X		X	X	X
Methyl Methacrylate (CAS 80-62-6)		X	X	X	X	X
Methacrylic Acid (CAS 79-41-4)		X			X	

International Regulations

DSL (Canada): Components of this product are listed. Benzoyl Peroxide (CAS 94-36-0); Methyl Methacrylate (CAS 80-62-6); Methacrylic Acid (CAS 79-41-4)

EINECS: Not Available.

WHMIS: B2, C, D2B.

Section 16 OTHER INFORMATION

Changes to This Revision: Original

Prepared By: Charles Hann
Telephone: USA – 877-422-4583
Internet: john@aaaglue.com

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT