

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: FORMICA HARDSTOP F-285-ACT-AA

Product Name: FORMICA HARDSTOP REACTIVATOR

Revision Date: Oct 07, 2019 Date Printed: Oct 07, 2019

Version: 1.0 Supersedes Date: N.A.

Manufacturer's Name: Choice Adhesives

Address: 666 Redna Terrace Cincinnati, OH 45215

Emergency Phone: CHEMTREC US: 1-800-424-9300, INTERNATIONAL CALLS: 1-703-527-3887

Information Phone Number: 1-800-330-5566

Fax:

Product/Recommended Uses:

SECTION 2) HAZARDS IDENTIFICATION

Classification

Acute toxicity Oral - Category 5

Aerosols Category 1

Eye Irritation - Category 2A

Skin Irritation - Category 3

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms





Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

Hazardous Statements - Health

H303 - May be harmful if swallowed.

H319 - Causes serious eye irritation.

H316 - Causes mild skin irritation.

H336 - May cause drowsiness or dizziness.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

SAM#5855 Page 1 of 8

Precautionary Statements - Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P233 Keep container tightly closed.

Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P403 + P405 Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Hazards Not Otherwise Classified (HNOC)

None.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000067-64-1	ACETONE	79% - 100%
0000124-38-9	CO2	4% - 8%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed/lf you feel unwell/lf concerned: Call a POISON CENTER/doctor.

Eliminate all ignition sources if safe to do so.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

IF exposed or concerned: Get medical advice/attention.

Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery

SAM#5855 Page 2 of 8

position.

Most Important Symptoms and Effects, Acute or Delayed

No data available.

Immediate Medical Attention and Special Treatment, if necessary

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Do not direct a solid stream of water or foam into hot, burning pools this may results in frothing and increase fire intensity.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

Fire-Fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning Up

Absorb liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SAM#5855 Page 3 of 8

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them.

Store at temperatures below 120°F.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over- boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
ACETONE	1000	2400			1			250
CO2	5000	9000			1			5000

Chemical Name	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
ACETONE	590				250		500	
CO2	9000	30000	54000		5000		30000	

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density VOC Less H2O and Exempts 0.00000 lb/gal

SAM#5855 Page 4 of 8

 VOC Actual(g/l)
 0.00000 g/l

 VOC Regulatory(g/l)
 0.00000 g/l

 VOC Regulatory(lb/gal)
 0.00000 lb/gal

 Density
 6.80000 lb/gal

 Density VOC
 0.00000 lb/gal

 % VOC
 0.00000%

Appearance Colorless
Odor Threshold N.A.
Odor Description Acetone
pH N.A.
Flammability N/A

Water Soluble in water

Flash Point Symbol N.A. Flash Point N.A. Viscosity N.A. Lower Explosion Level N.A. Upper Explosion Level N.A. Vapor Pressure N.A. Vapor Density N.A. Freezing Point N.A. Melting Point N.A. Low Boiling Point N.A. High Boiling Point N.A. Auto Ignition Temp N.A. **Evaporation Rate** N.A. VOC Composite Partial Pressure N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal storage and handling conditions.

Hazardous Reactions/Polymerization

Will not occur.

Incompatible Materials

Avoid strong oxidizers, reducers, acids, and alkalis.

Conditions to Avoid

Avoid heat, sparks, flame, high temperature and contact with incompatible materials. Dropping containers may cause bursting.

Hazardous Decomposition Products

No data available.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely Route of Exposure

Inhalation, ingestion, skin absorption.

Skin Corrosion/Irritation

Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

Causes mild skin irritation.

SAM#5855 Page 5 of 8

Can cause skin irritation.

Serious Eye Damage/Irritation

Eye contact may lead to permanent damage if not treated promptly.

Liquid or vapors may irritate the eyes.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly.

Causes serious eye irritation.

0000067-64-1 ACETONE

Exposure can irritate the eyes.

Respiratory/Skin Sensitization

0000067-64-1 ACETONE

Can irritate the nose and throat causing coughing and wheezing.

Germ Cell Mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness.

0000067-64-1 ACETONE

May affect the kidneys and liver.

Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

No data available.

Aspiration Hazard

No data available.

Acute Toxicity

If inhaled, may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heart beats.

May be harmful if swallowed.

Potential Health Effects - Miscellaneous

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

Likely Routes of Exposure

0000067-64-1 ACETONE

Substance can be absorbed into the body by inhalation.

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m3 (4-hour exposure) (29) LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m3 (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31) LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32,unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

SAM#5855 Page 6 of 8

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No data available.

Persistence and Degradability

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable.

Bio-accumulative Potential

No data available.

Mobility in Soil

0000067-64-1 ACETONE

The substance is not PBT / vPvB

The substance is not PBT / vPvB.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Ground Transportation: (Continental United States, Canada & Mexico): Limited Quantity

IMDG Information

Shipping Name: Aerosols UN/NA #: 1950 Hazard Class: 2.1

Required Placard: Limited Quantity Marine Pollutant: No data available

IATA Information

We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000067-64-1	ACETONE	79% - 100%	DSL,CERCLA,SARA312,VOC_exem pt,TSCA,RCRA
0000124-38-9	CO2	4% - 8%	DSL,SARA312,TSCA

SECTION 16) OTHER INFORMATION

Glossary

SAM#5855 Page 7 of 8

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; N.A. - Not Available; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; Sarka 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

Version 1.0:

Revision Date: Oct 07, 2019 First Edition.; First Edition.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

SAM#5855 Page 8 of 8